



TECHNICAL DATA SHEET

Product Code	CFA-017
Product Description	A single-component, water-based skimming plaster formulated from a blend of acrylic polymers and fillers, suitable for both interior and exterior applications.
Intended Uses	- Skims walls, gypsum and fibre cement boards. - Fills hairline cracks.
Features & Benefits	- Ready Mixed - No priming is necessary if surfaces are properly prepared and free of dust - Smooth matt appearance
Product Information	Appearance: Smooth Matt Colours: Off White Solids: Approx.68 – 70 % by volume Appro. 48 – 50 % by weight Density: Approx. 1.65 kg/ltr Spreading Rate: 1 - 2 m²/kg depending on if grain filling or skimming is required Flash Point: Non – Flammable Binder Type: Acrylic Emulsion This product is manufactured under strict SABS ISO 9001 : 2015 quality standards.
Application Details	Mixing: Ready-mixed. Mix thoroughly before use. Method: Spackle tool and/or trowel Thinning: Not Recommended Cleaning: Water clean-up Drying Time: Touch dry : 1.5- 2 Hours – Depending on temperature and humidity 16 Hours – Depending on climatic condition. Cooler temperature extends drying times. Re-coating Time:
Surface Preparation	All surfaces to be coated should be free of contaminants such as water, rust, dirt, oil, grease or loose particles. Moisture levels should be below 15% moisture content - Use a scraper to open all cracks. Scrape off excess plaster and high points, and eliminate any loose or flaking debris. - Repair surface cracks, holes or damaged plaster with Prostar Wallfix Crackfiller. - Touch in nails and screw heads with an appropriate ProStar Anticorrosive primer. - Powdery/friable plaster should be primed with a ProStar 4 in 1 Plaster Primerseal to aid adhesion. Application Instructions: - Apply ProStar ProSkim using a wet plastering trowel, skimming tool, or large scraper. Work in an upward, curved motion while maintaining firm, even pressure. - Apply only the amount of ProStar ProSkim required. For best results, build up the film thickness in multiple thin layers rather than one thick coat (maximum thickness: 5mm). Minor surface irregularities or 'tramlines' can be corrected in subsequent layers. - Once touch dry (after 20–30 minutes), use a clean damp sponge to refine edges, remove high spots, and eliminate excess material. - Allow 2 hours to dry and if required use a medium grit sand paper to sand smooth.
Precautions	- Do not apply during inclement of extreme weather conditions: - wet, below 10°C or above 35°C - Relative humidity above 80 % - Temperature Lower than 3°C of dew point - Not suitable for metal surfaces. - Not suitable for direct application to powdery or friable surfaces whether previously painted or not.
Safety Precautions	- Keep out of reach of children. - If product is ingested seek immediate medical advice. - In case of eye contact seek medical attention. - Ensure that product is stored in a cool dry. - Wear a suitable dust mask if sanding. - To avoid any risk of spillage, always transport in a secure upright position.



TECHNICAL DATA SHEET

Storage Conditions

- Store in a cool, dry place away from direct sunlight or extreme cold.
 - When not in use, sprinkle a small amount of water on the surface to prolong storage.
 - Open containers should not be stacked
-

Disclaimer:

The recommendations contained herein are given in all good faith and are meant to guide the specify or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No Guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

DURBAN – MANUFACTURING

262 Inanda Road,
Springfield Park
Tel: 031 574 5376
From outside RSA: +27 31 574 5376

DURBAN – SALES

81 Moses Kotane Rd
Overport
Tel: 031 207 1133
From outside RSA: +27 31 207 1133

RICHARDS BAY - SALES

121/3 Dollar Drive, Shop 9
Richards Bay Central
Tel: 035 760 1166
From outside RSA: +27 35 760 1166

CAPE TOWN – SALES

Aster Industrial Park,
53 Socony Rd, Parow
Tel: 021 532 1535
From outside RSA: +27 21 532 1535

JOHANNESBURG - SALES

Unit 5, Criscon Park, 112 Richards Drive,
Halfway House, Midrand
Tel: 010 224 0180
From outside RSA: +27 10 224 0180

Email: Info@prostarpaints.co.za
