

Section 1. Identification

GHS product identifier	Bituminous Aluminium for Torch on
Other means of identification	WPSBC-005-A
Product type	Liquid
Relevant identified uses of the substance or mixture and uses advised against	
Product Use	A single-component aluminium paint based on bitumen and alkyd, offering outstanding flow and a brilliant finish.
Supplier's details	Prostar Export Paint PTY (Ltd) 268 Inanda Road, Springfield Park Durban Tel: +27 31 574 5376
Emergency Telephone number	National Poison Centre: 0861 555 777

Section 2. Hazard identification

Classification of the Substance or Mixture	FLAMMABLE LIQUID - Category 3 SERIOUS EYE DAMAGE/ IRRITATION - Category 1 SKIN CORROSION/ IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE - Category 3 ASPIRATION HAZARD - Category 1 RESPIRATORY SENSITIZATION - Category 1 ACUTE TOXICITY (ORAL) - Category 4 ACUTE TOXICITY (INHALATION) - Category 4 ACUTE TOXICITY (DERMAL) - Category 4 AQUATIC TOXICITY (CHRONIC) - Category 2 UN GHS
Label elements according to	
Hazard pictograms	    
Signal word	Danger H226 - Flammable liquid and vapour. H302 - Harmful if swallowed. H304 - May be fatal if swallowed and enters airways. H312 - Harmful if in contact with skin. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H332 - Harmful if inhaled. H334 - May cause allergy or asthma symptoms or breathing difficulties if Inhaled H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long-lasting effects.
Hazard statements	
Precautionary statements:	
General	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions.
Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P233 - Keep container tightly closed. P261 - Avoid breathing dust/fumes/gas/mist/vapours/spray. P262 - Do not get in eyes, on skin, or on clothing. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection or face protection.

Section 2. Hazard identification

Response

P285 - in case of inadequate ventilation wear respiratory protection.
P235 + 410 - Keep cool. Protect from sunlight.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P333+317 - If skin irritation or rash occurs get medical help.
P337+317 - If eye irritation persists get medical help.
P361+364 - Take off immediately all contaminated clothing and wash it before reuse.
P370+378 - In case of fire: Use fire extinguisher.
P391 - Collect spillage. Hazardous to the aquatic environment.
P410 - Protect from sunlight.
P402+404 - Store in a dry place. Store in a closed container.
P403+235 - Store in a well-ventilated place. Keep cool.

Storage

Disposal

P501 - Dispose of contents and container in accordance with all local regulation.

Other Hazards which do not result in Classification

None Identified

Section 3. Composition/information on ingredients

Substance / mixture

Mixture

Other means of identification

DSBC-008/ 010/ 016

CAS number/other identifiers

CAS Number

Not Applicable

Ingredient name	CAS number	%	SANS 10234 Classification
Toluene	108-88-3	20.0 - 25.0	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 5, H303 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Aquatic Chronic. 2, H411 Asp.Haz.1, H304 STOT - SE. 3, H335
Phthalic Anhydride	85-44-9	2.0 - 5.0	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 1, H318 Resp. Sen. 1, H334 Skin Sens. 1, H317 STOT - SE. 3, H335
Aluminium powder	7429-90-5	15.0-20.0	Flam. Sol. 1, H228 Water-react. 2, H261
Xylene	1330-20-7	<2.00	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation persists.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	Remove contaminated clothing and shoes. Wash contaminated skin with soap or a recognised skin cleaner and plenty of water. Avoid the use of solvents. Get medical attention if symptoms persist. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Remove victim to fresh air and keep at rest in a position Comfortable for breathing. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	Causes eye irritation.
Inhalation	Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	Harmful if swallowed. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Eye contact	Adverse symptoms may include pain or irritation, watering or redness.
Inhalation	Adverse symptoms may include nausea or vomiting, headache, drowsiness/ fatigue or dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths skeletal malformations.
Skin contact	Adverse symptoms may include irritation or redness, reduced fetal weight, increase in fetal deaths, skeletal malformations.
Ingestion	Adverse symptoms may include pain or irritation, reduced fetal Weight, increase in fetal deaths, skeletal malformations.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without Suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Use an extinguishing agent suitable for the surrounding fire such as dry powder, CO₂, water spray (fog) or foam. Use fog to cool and control.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemicals

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

Carbon dioxide
Carbon monoxide
Metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safehandling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges.

Conditions for safe storage,including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.

Section 8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name	Exposure limits
Toluene	OHSA: LTEL: 100 ppm; 375 mg/m ³ STEL: 150 ppm; 560 mg/m ³
Aluminium powder	OHSA: TWA: OEL-RL: 5 mg/m ³ . Form: Respirable dust TWA: OEL-RL: 10 mg/m ³ . Form: Total inhalable dust
Xylene	OHSA: TWA: OEL-RL 100 ppm; 435 mg/m ³ STEL: OEL-RL 150 ppm; 650 mg/m ³

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Appropriate engineering controls

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

BITUMINOUS ALUMINIUM FOR TORCH ON SAFETY DATA SHEET

According to GHS

Eye/face protection

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Body protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Other skin protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary e.g. in case of insufficient ventilation. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state	Liquid
Color	Opaque Silver
Odor threshold	No data available
Melting point	Not applicable
Boiling point	No data available
Flammability (solid, gas)	No data available
Lower and upper explosive (flammable) limits	No data available
Flash point	38 °C
Auto-ignition temperature	No data available
Decomposition temperature	No data available
pH	Not applicable
Viscosity	40 - 50 KU
Solubility	Soluble in organic solvents, insoluble in water
Partition coefficient: n-octanol/water	No data available
Evaporation rate	No data available
Vapour pressure	No data available
Relative density	0.95 – 1.00 g/ml (typical)
Vapour density	No data available
Particle characteristics	No data available

Section 10. Stability and reactivity

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No data available

Incompatible materials

No data available

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Acute Toxicity

Ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation	Rat	20 mg/l	4 hours
	LD50 Oral	Rat	>7000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Aluminium powder	LC50 Inhalation	Rat	> 5 mg/l	-
	LD50 Oral	Rat	2000 mg/kg	-
	LD50 Dermal	Rat	2000 mg/kg	4 hours
Xylene	LC50 Inhalation Gas	Rat	5000 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-

Irritation/Corrosion

Ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Skin - Irritation Eyes - Irritation	Rabbit Rabbit	3	-	Mild irritant
			12	24 hours	Non-irritant
			18	48 hours	
			18	72 hours	
			16	4 days	
			9	7 days	
Aluminium powder	Eyes - Irritation	Rabbit			Mild irritant
	Skin - Irritation	Rabbit			irritant
Xylene	Skin - Irritation	Rabbit	-	87 mg	Mild irritant
	Eye - Irritation	Rabbit	-	100 %	Moderate irritant

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

Information on the likely routes of exposure

Inhalation, skin and eye contact.

Potential acute health effects

Eye contact

Causes serious eye damage.

Inhalation

Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Skin contact

Harmful in contact with skin. May cause an allergic skin reaction.

Ingestion

Maybe harmful if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

BITUMINOUS ALUMINIUM FOR TORCH ON

SAFETY DATA SHEET

According to GHS

Eye contact	Adverse symptoms may include pain or irritation, watering or redness.
Inhalation	Adverse symptoms may include nausea or vomiting, headache, drowsiness/ fatigue or dizziness/vertigo.
Skin contact	Adverse symptoms may include irritation or redness.
Ingestion	May cause damage to organs through prolonged or repeated exposure.
<u>Potential chronic health effects</u>	
General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Section 11. Toxicological information

Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Acute toxicity estimates	No data available.

Section 12. Ecological information

Toxicity

Ingredient name	Result	Species	Exposure
Toluene	Acute LC/EC50 8.1 mg/l Fish	Salmon	96 hours
	Acute LC/EC50 6.0 mg/l Aquatic	Daphnia magna	48 hours
	Acute LC/EC50 9.4 mg/l Algae	Green algae	8 hours
Aluminium powder	Acute LC/EC50 ≤ 100 mg/l Fish	Pimephales promelas	96 hours
	Acute LC/EC50 ≤ 100 mg/l Aquatic	Daphnia magna	48 hours
	Acute LC/EC50 ≤ 10 mg/l Algae	Green algae	8 hours
	Acute LC/EC50 ≤ 100mg/l Bacteria	Pseudomonas putida	16 hours
Xylene	Acute LC50 8500 ug/l Aquatic	Crustaceans - Palaemonetes	48 hours
	Acute LC50 3300 to 4093 ug/l Fish	Pugio Oncorhynchus mykiss -0.6 g	96 hours

Persistence and degradability

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
------------------------	--------------------------	-------------------	-------------------------

No available data

Bioaccumulative potential

Ingredient name	LogPow	BCF	Potential
------------------------	---------------	------------	------------------

No available data

Mobility in soil

Soil/water partition coefficient (KOC)

No data available.

Mobility

No data available.

PBT/vPvB data

P: No data available.
B: No data available.
T: No data available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any

Section 13. Disposal considerations

regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	Transportation - road - SANS 10228:2012	Transportation Maritime - IMO/ IMDG	Transportation- Air – IATA
UN number	1263	1263	1263
UN proper shipping name	Paint	Paint (Solvent naphtha (petroleum), medium aliph)	Paint
Transport hazardclass(es)	3 	3 	3 
Packing group	III	III	III
Environmental hazards	Environmentally hazardous	Marine pollutant	Environmentally hazardous
Additional information	No data available	Emergency schedules (EmS) F-E, S-E	Passenger and Cargo Aircraft Ltd QTY: Quantity limitation: 10 L Packaging instructions: Y344 Cargo Aircraft Only: Quantity limitation: 220 L Packaging instructions: 366 Limited Quantities – Passenger Aircraft Quantity limitation: 60L Packaging instructions: 355
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No data available	No data available	No data available



BITUMINOUS ALUMINIUM FOR TORCH ON SAFETY DATA SHEET

According to GHS

Section 15. Regulatory information

Safety, health and environmental regulationsspecific for the product

Relevant information regarding authorization: Occupational Health and Safety Act 1993 Regulation for Hazardous Chemical Substances.

Relevant information regarding restrictions: None known. EU regulations: Regulation EC 1272/2008 [EU-GHS/CLP] and EU directives 67/548/EEC or EC 1999/45/EC

Section 15. Regulatory information

Other National regulations: None. Standards used for PPE recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166- European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

Section 16. Other information

History

Date of review

No Previous Version

Date of review	Version	Amendments
30/04/2025	1	Initial Version

Date of previous issue Version:

Key to abbreviations

ATE = Acute Toxicity Estimate
BCP Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OHSA = Occupational Health and Safety Act, 1993 (South Africa)
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
UN = United Nations
Supplier Safety Data Sheets.

References

Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Notice to readers:

Employers should use this information only as a supplement to other information gathered by them and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.